

HIGH PERFORMANCE ACRYLIC PROTECTIVE & DECORATIVE COATING FOR CONCRETE & MASONRY

DESCRIPTION

Elastodeck S is a single component acrylic copolymer water based protective coating with excellent resistance to aggressive environments. It is available in a range of colours.

USES & ADVANTAGES

Use to protect reinforced concrete structures from attack by atmospheric gases, chloride ions, sulphates, oxygen and water. It may be used on new or existing concrete and masonry structures and is specially suitable in aggressive marine and coastal environments.

Advantages include:-

- Allows water vapour to escape from structure.
- Excellent resistance to UV and long term weathering.
- Highly durable in all climatic conditions.
- Excellent barrier to chloride ions, sulphates, carbon dioxide, oxygen & water.
- Broad range of colours.
- Non toxic.
- Easy clean up.
- No solvents, no pungent smell or hazard.
- Can apply to various substrates including wood.

PROPERTIES

Volume Solids :	50%
Specific Gravity :	1.28 - 1.31
Reduction in chloride ion penetration :	>99%
Freeze/thaw salt scaling :	Unaffected
Chloride ion diffusion :	None after 2 years
accelerated weathering	immersion
Elongation :	>800% at 24°C
Fully dried :	5-7 days

** Properties are typical under laboratory conditions and do not constitute a specification. Field trials are recommended.*

SURFACE PREPARATION

The surface must be sound, dry & clean with no contamination. Remove oil, grease, loose particles, moss, algae, surface laitance and any remaining traces of mould oil or curing compounds. The surface may be achieved by lightly grit or water blasting. If water blasting the surface must be dry before application. Where mosses or algae were present the surface should be cleaned with a biocide after cleaning. Before over coating of existing coatings undertake bond tests both existing coating to concrete & **Elastodeck S** to old coating.

All blow holes or minor surface defects should be made good using **Conpatch 300**, honey combs should be repaired with **Conpatch 600**. Repair materials should dry for at least 48 hours depending on climatic conditions before application.

APPLICATION

To achieve the protective properties of **Elastodeck S** ensure that application rates are followed.

	Primer	Elastodeck S
Number of Coats	Flood coat	2
Application rate	7.14 m ² / ltr	3 m ² / ltr
Wet film thickness	NA	300 microns/coat
Dry film thickness	NA	150 microns/coat
Overcoating time		
@20°C	2 hours	8 hours
@30°C	90 mins	6 hours

All areas to be protected should be masked with masking tape. Do not apply if the temperature is less than 2°C. The primer should be applied by knapsack spray at 0.4 litres/m² in one or two coats and left to dry for at least 2 hours at 20°C before the application of **Elastodeck S**. Do not apply **Elastodeck S** until the primer is dry.

Apply **Elastodeck S** by brush, roller or spray.

Stir the material thoroughly before use, the first coat should be applied using suitable equipment to achieve a uniform coating with a wet film thickness not less than 300 microns. The first coat should dry before applying the second. Apply the second coat as above to achieve a wet film thickness not less than 300 microns.

CLEANING

Elastodeck S may be removed by using water whilst **Elastodeck S Primer** should be removed with solvents.

LIMITATIONS

Elastodeck S is produced to apply over sound concrete, masonry and wood surfaces. If applied over an existing coating trials should be conducted to ensure compatibility & bond.

STORAGE & SHELF LIFE

All products have a shelf life of 12 months if kept stored in original unopened packaging. Store in cool, dry conditions away from sources of heat & flames in the original packaging. If stored at high temperatures or humidity the shelf life may be reduced.

HEALTH & SAFETY

Elastodeck S and primer should be applied with adequate ventilation avoid inhalation of vapours.

Wear suitable protective clothing, glasses & eye protection. In confined areas use suitable respiratory protective equipment.

If swallowed do **NOT** induce vomiting - give a glass of water. If in eyes, hold eyes open, flush with water for at least 15 minutes.

Elastodeck S



HIGH PERFORMANCE ACRYLIC PROTECTIVE & DECORATIVE COATING FOR CONCRETE & MASONRY

Elastodeck S is non-flammable. **Elastodeck S Primer** is flammable, keep away from sources of ignition. No smoking, in the event of fire, extinguish with CO₂ or foam.

PACKAGING

20 Litre pails.

TECHNICAL SERVICE

The Cormix International Technical Service Department is available to assist you in the correct use of our products and its resources are at your disposal entirely without obligation.

QUALITY ASSURANCE

ISO 9001 : 2008 verified by TUV Nord

CONTACT DETAILS

Cormix International Limited

Regional Office,

89 Romklao Rd., Sansab, Minburi, Bangkok 10510

Tel. (66 2) 917 3955-8, 543 8890

Fax. (66 2) 917 3959, 543 8891

<http://www.cormix.com> E-mail : info@cormix.com

NOTE : Every reasonable precaution is taken in the manufacture of all CORMIX-products to ensure that they comply with CORMIX's high standard of quality. The recommendations and properties of the product are based upon what is believed to be the most reliable information available, and are not intended as recommendations which infringe on other patents. Although all CORMIX-products are subject to rigid quality tests, no specific guarantee can be given, because results depend, not only on quality, but also on other factors beyond our control. We welcome therefore consultation in the event of doubt concerning application, or performance, and point out that oral recommendations, which vary from the instructions contained herein, are not binding without written confirmation by CORMIX. All transactions shall be subject to our terms and conditions of sale-delivery-and-service. This data sheet supersedes the previous one and a reprint may be issued without notice to supersede this edition, as and when deemed necessary. The information given in this leaflet is to the best of our knowledge true and reliable. Field service where provided does not constitute supervisory responsibility. Our guarantee is therefore limited to the quality of materials delivered.