

Contite[®] Waterstop Adhesive



BONDING AGENT FOR HYDROPHILIC CONSTRUCTION JOINT WATERSTOPS

DESCRIPTION

Contite Waterstop Adhesive is a non-flammable, waterbased adhesive especially formulated to work with **Contite Waterstop** concrete construction joint waterstops.

USES

Contite Waterstop Adhesive is used to secure **Contite Waterstop** to concrete, metal, wood, and PVC surfaces on both vertical and horizontal applications, as well as around through wall mechanical and plumbing penetrations.

TYPICAL PROPERTIES

Appearance : Milky white
S.G. : 1.01-1.03
pH : 9-10

INSTALLATION

Clean the substrate surface prior to application of **Contite Waterstop Adhesive**.

Roller or brush apply a minimum of 0.1 mm. thick, and at least the width of the chosen **Contite Waterstop** profile over the entire surface length to receive **Contite Waterstop**. Allow to dry for 10-15 minutes, or in damp environments allow a longer period to dry.

After adhesive has dried (become tacky), press the entire length of **Contite Waterstop** firmly onto the adhesive. Press firmly a minimum of 15 seconds - especially at the highest coil end on vertical applications.

COVERAGE RATE

Application Rate: One pail per 120 - 180 m. at 0.1 mm. thick by 25 mm. width.

LIMITATIONS

Substrate surface must be clean and sound.
Concrete curing compounds should not contain oil, wax or pigments. Do not allow to freeze prior to use.
Any remaining curing compound should be removed by wire brush.

PACKAGING

5 litre plastic pails.

STORAGE & SHELF LIFE

Contite Waterstop Adhesive should be stored protected from sunlight and frost. The shelf life is at least 6 months in original unopened containers.

HEALTH & SAFETY

There are no known hazards associated with **Contite Waterstop** during normal use. Refer to product material safety data sheet.

TECHNICAL SERVICE

The Cormix International Technical Service Department is available to assist you in the correct use of our products and its resources are at your disposal entirely without obligation.

QUALITY ASSURANCE

ISO 9001 : 2008 verified by TUV Nord.

CONTACT DETAILS

Cormix International Limited

Regional Office,
89 Romklat Road, Sansab, Minburi, Bangkok 10510
Tel. (66 2) 917 3955-8, 543 8890
Fax. (66 2) 917 3959, 543 8891
<http://www.cormix.com> E-mail : info@cormix.com

Rev. 003 : May 2010

NOTE : Every reasonable precaution is taken in the manufacture of all CORMIX-products to ensure that they comply with CORMIX's high standard of quality. The recommendations and properties of the product are based upon what is believed to be the most reliable information available, and are not intended as recommendations which infringe on other patents. Although all CORMIX-products are subject to rigid quality tests, no specific guarantee can be given, because results depend, not only on quality, but also on other factors beyond our control. We welcome therefore consultation in the event of doubt concerning application, or performance, and point out that oral recommendations, which vary from the instructions contained herein, are not binding without written confirmation by CORMIX. All transactions shall be subject to our terms and conditions of sale-delivery-and-service. This data sheet supersedes the previous one and a reprint may be issued without notice to supersede this edition, as and when deemed necessary. The information given in this leaflet is to the best of our knowledge true and reliable. Field service where provided does not constitute supervisory responsibility. Our guarantee is therefore limited to the quality of materials delivered.