

Contite® Waterstop Adhesive

BONDING AGENT FOR HYDROPHILIC CONSTRUCTION JOINT WATERSTOPS

DESCRIPTION

Contite Waterstop Adhesive is a non-flammable, waterbased adhesive especially formulated to work with **Contite Waterstop** concrete construction joint waterstops.

USES

Contite Waterstop Adhesive is used to secure **Contite Waterstop** to concrete, metal, wood, and PVC surfaces on both vertical and horizontal applications, as well as around through wall mechanical and plumbing penetrations.

TYPICAL PROPERTIES

Appearance : Milky white

S.G. : 1.01-1.03

pH : 9-10

INSTALLATION

Clean the substrate surface prior to application of **Contite Waterstop Adhesive**.

Roller or brush apply a minimum of 0.1 mm. thick, and at least the width of the chosen **Contite Waterstop** profile over the entire surface length to receive **Contite Waterstop**. Allow to dry for 10-15 minutes, or in damp environments allow a longer period to dry.

After adhesive has dried (become tacky), press the entire length of **Contite Waterstop** firmly onto the adhesive.

Press firmly a minimum of 15 seconds - especially at the highest coil end on vertical applications.

COVERAGE RATE

Application Rate: One pail per 120 - 180 m. at 0.1 mm. thick by 25 mm. width.

LIMITATIONS

Substrate surface must be clean and sound.

Concrete curing compounds should not contain oil, wax or pigments. Do not allow to freeze prior to use.

Any remaining curing compound should be removed by wire brush.

PACKAGING

5 litre plastic pails.

STORAGE & SHELF LIFE

Contite Waterstop Adhesive should be stored protected from sunlight and frost. The shelf life is at least 6 months in original unopened containers.

HEALTH & SAFETY

There are no known hazards associated with **Contite Waterstop** during normal use. Refer to product material safety data sheet

TECHNICAL SERVICE

The Cormix International Technical Service Department is available to assist you in the correct use of our products and its resources are at your disposal entirely without obligation.

QUALITY ASSURANCE

ISO 9001 : 2008 verified by TUV Nord.

CONTACT DETAILS

Cormix International Limited

89 Romklat Rd., Sansab, Minburi, Bangkok 10510

Tel. (66 2) 917 3955-8, 543 8890

Fax. (66 2) 917 3959, 543 8891

<http://www.cormix.com>

E-mail: info@cormix.com

Rev.004 Oct 2018