

**AIR ENTRAINING CONCRETE ADMIXTURE****DESCRIPTION**

**Conair** is a liquid air entraining agent for use in concrete and mortar mixes. It is used to improve the workability, cohesion, and durability of concrete and mortar by the entrainment of minute air bubbles of controlled size and spacing, uniformly distributed throughout the mix. **Conair** complies with ASTM C260-81 for air entraining admixtures. It provides freeze thaw protection in cold climates.

**USES & ADVANTAGES**

Conair is used to produce workable and durable concrete for dams and reservoirs, tunnels, mass concrete structures, roads, runways, taxiways etc.

**Advantages include:-**

- Improves permeability
- Improves workability.
- Improves durability.
- Cohesion of mixes is improved and bleeding reduced.
- Volume yield of concrete or mortar is increased.
- Harsh mixes are improved.
- Easy to use.
- Ready to use.
- Freeze thaw protection.

**PROPERTIES**

**Appearance:** Light brown liquid

**Specific Gravity:** Approx. 1.0 kg/ltr

**Storage:** Free from frost in shade.  
Reseal after use.

**pH Value:** 8-10

**DEPENSING/APPLICATION**

**Conair** is added directly to the mixing water prior to its addition to the aggregates. **Conair** can be used with other admixtures providing these are added separately to the mix. Do not pre-mix.

**IMPORTANT NOTES**

Overdosing will result in a high air content with resulting reductions in strength. To ensure consistent results air contents should be regularly monitored particularly if other materials are subject to variation.

**DOSAGE**

The dosage of **Conair** normally is in the range of 0.03 - 0.2 litre per 100 kg of total cementitious material, however, there is no standard dosage. The dosage level is not predictable because of varying materials and concrete mix designs.

Factors influencing air entrainment are: cement quality, sand grading, sand to aggregate ratio, slump, temperatures, cement replacements or pozzolanic materials such as PFA, GGBFS or silica fume.

Trial mixes may be started at 0.1% by weight of cement and the dosage adjusted depending on the results obtained under actual job conditions.

Mixes containing other plasticisers/retarders may require less air entrainer than plain mixes. Vary the dosage until the desired effect is achieved.

**PACKAGING**

25 litre plastic pails and 200 litre drums.

**STORAGE & SHELF LIFE**

Shelf life up to 12 months if stored in original unopened package in shaded conditions.

**HEALTH & SAFETY**

As with all chemical products care should be taken during use and storage to avoid contact with skin eyes and mouth.

If accidentally ingested immediately seek prompt medical attention, do not induce vomiting and give copious amounts of water to drink.

**TECHNICAL SERVICE**

The Cormix International Technical Service Department is available to assist you in the correct use of our products and its resources are at your disposal entirely without obligation.

**QUALITY ASSURANCE**

ISO 9001 : 2015 verified by TUV Nord.

ISO 14001 : 2015 verified by Lloyd's Register International.

**AIR ENTRAINING CONCRETE ADMIXTURE****DISCLAIMER**

Performance data is achieved testing in accordance with International Standards. Testing by others may result in different results from those published as a result of external factors such as poor sampling, incorrect mixing, varying temperatures, curing, crushing procedures etc.

Cormix does not take responsibility nor need to defend others testing that does not achieve the published data. The user must test the products suitability for the intended application and purpose. Cormix reserves the right to change the properties of the product.

Site conditions and differences in materials are such that no warranty or fitness for a particular purpose, nor liability can be inferred from the published data sheet, written recommendations or from other advice offered.

**CONTACT DETAILS****Cormix International Limited**

89 Romklao Rd., Sansab, Minburi, Bangkok 10510

Tel. (66 2) 917 3955-8

Fax. (66 2) 917 3959

<http://www.cormix.com>

E-mail: [info@cormix.com](mailto:info@cormix.com)

**NOTE :** Every reasonable precaution is taken in the manufacture of all CORMIX-products to ensure that they comply with CORMIX's high standard of quality. The recommendations and properties of the product are based upon what is believed to be the most reliable information available, and are not intended as recommendations which infringe on other patents. Although all CORMIX-products are subject to rigid quality tests, no specific guarantee can be given, because results depend, not only on quality, but also on other factors beyond our control. We welcome therefore consultation in the event of doubt concerning application, or performance, and point out those oral recommendations, which vary from the instructions contained herein, are not binding without written confirmation by CORMIX. All transactions shall be subject to our terms and conditions of sale-delivery-and-service. This data sheet supersedes the previous one and a reprint may be issued without notice to supersede this edition, as and when deemed necessary. The information given in this leaflet is to the best of our knowledge true and reliable. Field service where provided does not constitute supervisory responsibility. Our guarantee is therefore limited to the quality of materials delivered.