

Constrip® 4

HIGH PERFORMANCE MOULD OIL

DESCRIPTION

A premium mould oil specifically developed for harsh conditions in tropical climates where high performance is required. **Constrip 4** gives excellent resistance to tropical rain and performs well where steel moulds have high surface temperatures. A ready to use liquid which out performs standard mould oils.

Constrip 4 is an emulsified product based on a blend of selected high quality paraffin solids and oils.

USES & ADVANTAGES

Can be used with all types of moulds providing fast easy release and clean fair face concrete.

Advantages include:-

- Reduces or eliminates bubbles.
- Resistant to rain.
- Performs well with high surface temperatures.
- Ready to use.
- Produces clean fair face finish.
- High coverage rate.
- No staining to concrete surface.
- Spray or roller applied. Easy to clean.
- Non toxic.
- Does not rust moulds.
- Easy to release.
- Once applied long service life.
- Economical. Saves on bug hole and other surface repairs.

PROPERTIES

Appearance: White liquid
Specific Gravity: 0.95 - 1.02 kg/litre

APPLICATION

Constrip 4 is ready to use and shall be applied as thinly and evenly as possible. Apply by spray, roller or sponge, excess material should be removed by sponge before pouring concrete.

COVERAGE RATES

25 - 40 m² per litre depending on type of form-work.

PACKAGING

200 litre drums or 1,000 litre bulks.

STORAGE & SHELF LIFE

Constrip 4 should be stored protected from sunlight and frost. The shelf life is 9 months in original sealed containers.

HEALTH & SAFETY

Constrip 4 is formulated from materials that present no serious hazard to health provided normal protection and hygiene is maintained. Operators should wear protective clothing, gloves and goggles. Good ventilation is important in confined spaces or when spray applying. Wash off skin with plenty of soap and water. If in contact with eyes rinse immediately with clean water & seek medical attention.

TECHNICAL SERVICE

The Cormix International Technical Service Department is available to assist you in the correct use of our products and its resources are at your disposal entirely without obligation.

QUALITY ASSURANCE

ISO 9001 : 2015 verified by TUV Nord.
ISO 14001 : 2015 verified by Lloyd's Register International.

DISCLAIMER

Performance data is achieved testing in accordance with International Standards. Testing by others may result in different results from those published as a result of external factors such as poor sampling, incorrect mixing, varying temperatures, curing, crushing procedures etc.

Cormix does not take responsibility nor need to defend others testing that does not achieve the published data. The user must test the products suitability for the intended application and purpose. Cormix reserves the right to change the properties of the product. Site conditions and differences in materials are such that no warranty or fitness for a particular purpose, nor liability can be inferred from the published data sheet, written recommendations or from other advise offered.

CONTACT DETAILS

Cormix International Limited
89 Romklao Rd., Sansab, Minburi, Bangkok 10510
Tel. (66 2) 917 3955-8
Fax. (66 2) 917 3959
<http://www.cormix.com>
E-mail: info@cormix.com

Rev.008 Sep 2021