

# Contop® Plus E

A PREMIXED EMERY BASED MONOLITHIC SURFACE HARDENING COMPOUND

## DESCRIPTION

**Contop Plus E** is a premixed non rusting floor hardener used to form a monolithically hardened concrete floor. It gives an abrasion resistant and hard wearing surface and is applied by shake on methods.

## USES & ADVANTAGES

**Contop Plus E** is used to provide a hard wearing abrasion resistant surface. It is an extremely hard chemically inert aggregate based product and provides a non slip surface. Use in loading bays, trucking lanes, car parks, warehouse floors, repair and machine work-shops & production areas.

### Advantages include:-

- Forms a monolithic bond with concrete.
- Resistant to oil and grease.
- Does not rust.
- Easy and economical to apply.
- Various colours.
- Extremely strong, hard wearing abrasion and impact resistant floor.
- Performs to the same level of Al<sub>2</sub>O<sub>3</sub> based materials with contents in excess of 55%.
- Forms dense non porous extremely abrasion resistant floor.
- Contains very hard aggregates 9 on Moh's hardness scale.

## PROPERTIES

<b>Appearance:</b>	Grey or coloured powder. Colour may vary when applied.
<b>Composition:</b>	Suitable for use with all Portland cement including S.R.C.
<b>Abrasion Resistance:</b>	Tested to ASTM 779 B, ASTM D4060 Taber Test, ASTM C944, BS 6431 and BS 8204 Gives 250-300% improvement over plain concrete
<b>Moh Hardness:</b>	Aggregate 9
<b>Compressive Strength:</b>	In excess of 90 N/mm <sup>2</sup> ASTM C109 at 28 days

## APPLICATION

Once the freshly poured and leveled concrete has reached its plastic state the substrate should be smoothed using mechanical trowels. After bleed water has evaporated and concrete has a wet shine **Contop Plus E** should be sprinkled over the concrete surface at the recommended rate of application.

When the applied **Contop Plus E** appears uniformly moistened level out with a wood float or a power float. Finish with a steel trowel to obtain a smooth, uniform surface.

## COVERAGE RATES

Light Traffic 2-3 kg/m<sup>2</sup>  
 Medium Traffic 3-4 kg/m<sup>2</sup>  
 Heavy Traffic 4-5 kg/m<sup>2</sup>

## PACKAGING

25 kg. 4 Ply plastic lined bags.

## STORAGE & SHELF LIFE

Store in dry conditions in unopened bags.  
The shelf life is 6 months if stored correctly.

## HEALTH & SAFETY

Avoid inhalation of dust. Wear suitable protective clothing, gloves, eye protection and respiratory protection. In case of contact with eyes rinse immediately with plenty of clean water & seek medical advise. If swallowed seek medical attention immediately do not induce vomiting.

Fire: **Contop Plus E** is non flammable.

## TECHNICAL SERVICE

The Cormix International Technical Service Department is available to assist you in the correct use of our products and its resources are at your disposal entirely without obligation.

## QUALITY ASSURANCE

ISO 9001 : 2015 verified by TUV Nord.  
 ISO 14001 : 2015 verified by Lloyd's Register International.

## CONTACT DETAILS

**Cormix International Limited**  
 89 Romklao Rd., Sansab, Minburi, Bangkok 10510  
 Tel. (66 2) 917 3955-8  
 Fax. (66 2) 917 3959  
<http://www.cormix.com>  
 E-mail: [info@cormix.com](mailto:info@cormix.com)

Rev.010 Sep 2021